

日本 TOHNICHI 扭力起子 RTD(空轉式)



產品規格

精度±3%													
SI MODEL			RTD15CN		RTD30CN		RTD60CN		RTD120CN		RTD260CN	RTD500CN	
轉矩範圍 [CN•米]	MIN・~最大・		2~15		4~30		10~60		20~120		60~260	100~500	
	GRAD・		0.1		0.2		0.5		1		2	五	
計量模型			1.5RTD		3RTD		6RTD		12RTD		26RTD	50RTD	
轉矩範圍 [公斤力•厘米]	MIN・MAX~		0.2~1.5		0.4~3		1~6個		2~12		6~26	10~50	
	GRAD・		0.01		0.02		0.05		0.1		0.2	0.5	
美國模式			RTD20Z	RTD1.3I	RTD40Z	RTD2.6I	RTD80Z	RTD5I	RTD150Z	RTD10I	RTD22I	RTD40I	
扭矩範圍 [ozf•在/磅•在]	MIN・MAX~		ozf•在 6~20	llbf•在 0.2~1.3	ozf•在 15~40	磅•在 0.4~2.6	ozf•在 20~80	磅•在 1~5	ozf•在 30~150	磅•在 2~10	磅•在 6~22	10~40	
	GRAD・		ozf•在 0.2	磅•在 0.01	ozf•在 0.5	磅•在 0.02	ozf•在 1	磅•在 0.05	ozf•在 2	磅•在 0.1	磅•在 0.2	0.5	
適用絲鑽	小螺絲		(M1.8)		M2 (M2.2)		M2.5 , M3		(M3.5)		M4 (M4.5)	M5 , M6	
	自攻螺釘		(M1.4) M1.6		(M1.8) M2		(M2.2) M2.5		M3 (M3.5)		M4	(M4.5)	
DIMENSION [mm]的	總長度	L'	100				110		130		150	155	
	握	D1	16				20		35		44	33	
	身體	D2	10.7				14.8		18		23	26	
		D3	11										
		L1	18					24					
		L2	76.5~84.3					81.1~90.1		105~115		113.8~123.8	129~141
	儲物櫃	d	23.5				29		33		41	45	
		w ^	21.5				26.5		三十		37.5	41	
重量[kg]			0.05				0.08		0.16		0.27	0.32	

匡品企業有限公司
 QUINPIN ENTERPRISE CO., LTD.
 235 新北市中和區中山路2 段296 號12-之7
 Tel: 886-2-8245-6363 Fax: 886-2-8245-8313
 E-mail: quinpin.pro@msa.hine
<http://www.quinpin.com.tw>